

Acces. Uni Seal White PG 21 min 11.5 max



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 00 000 5092 |
| Specification | Acces. Uni Seal White PG 21 min 11.5 max |
| HARTING eCatalogue | https://b2b.harting.com/09000005092 |

Identification

| | |
|-------------------|-------------|
| Category | Accessories |
| Type of accessory | Cable gland |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +130 °C |
| Tightening torque | ≤15 Nm (depending on the cable and the seal insert used) |
| Wrench size | 30 |
| Degree of protection acc. to IEC 60529 | IP68 |
| Size | Pg 21 |
| Clamping range | 11.5 ... 15.5 mm |

Material properties

| | |
|-----------------------------|--|
| Material (cable glands) | Metal |
| Colour (accessories) | White |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |



Pushing Performance

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 65.17 g |
| Country of origin | Germany |
| European customs tariff number | 84849000 |
| eCl@ss | 27144432 Screwed cable gland (electr.) |