

Han 3 Quintax-F-c




Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 15 003 3101 |
| Specification | Han 3 Quintax-F-c |
| HARTING eCatalogue | https://b2b.harting.com/09150033101 |

Identification

| | |
|----------------|-----------------------------------|
| Category | Inserts |
| Series | Han-Brid [®] |
| Identification | Han-Brid [®] Quintax 3 A |

Version

| | |
|---------------------|---|
| Termination method | Crimp termination |
| Gender | Female |
| Size | 3 A |
| Number of contacts | 1 4 8 |
| Additional contacts | + shielding + 2 power contacts |
| Details | Please order crimp contacts separately. |

Technical characteristics

| | |
|-------------------------|------------------------------|
| Conductor cross-section | 0.14 ... 2.5 mm ² |
| Insulation resistance | >10 ¹⁰ Ω |
| Limiting temperature | -40 ... +70 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|-------------------|------------------------|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |



Pushing Performance

Material properties

| | |
|---|-----------|
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------------|--|
| Specifications | EN 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 14 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27440205 Contact insert for industrial connectors |