



∅F:
 Minimum cable diameter : 3
 Maximum cable diameter : -with rubber bushing : 6,5
 -without rubber bushing : 9,5

0967 037 0344	37	44,3	63,5	70,2	48	18,2	48,2	50,5	15,1	55,5	57,8	23,2	21	80°	16,1
0967 025 0344	25	27,8	47	53,7	45	15,2	31,7	47,5	12,1	39	41,4	25	16	80°	12,9
0967 015 0344	15	15,9	33,3	40	41	15,2	23,3	43,5	12,1	25,8	27,9	21	16	84°	-
0967 009 0344	9	14,9	25	31,6	39,5	15,2	20,1	42	12,1	17	19,4	23	12	-	-
Part number	No. of contacts	A±0,3	B±0,1	C±0,3	D±0,3	E±0,3	G±0,3	H±0,3	J±0,3	K±0,3	L±0,3	M±0,3	N±0,3	Q	R±0,3

All rights reserved Department EL PD HARTING (Zhuhai) Manufacturing Co., Ltd. 519085 Zhuhai, China	All Dimensions in mm Original Size DIN A3		Scale 2:1	Free size tol.		Ref. Sub.
	Created by ZHUANGJ	Inspected by LUOK	Standardisation 302077	Date 2021-07-07	State Final Release	
Title D-Sub Hood 09 to 37-pole top entry full metal						Doc-Key / ECM-Nr. 100521307/UGD/001/B 500000198749
Type TB		Number 09670XX0344			Rev. B	Page 1/1