

## Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	SMA-MALE RETURN LOSS (dB)	RIGHT ANGLE SMA-MALE RETURN LOSS (dB)
10.0	0.01	47.7	46.1
50.0	0.03	41.9	41.7
100.0	0.04	39.0	40.1
140.0	0.04	38.4	39.9
180.0	0.05	38.9	40.5
220.0	0.06	40.8	43.0
260.0	0.07	45.1	46.9
300.0	0.07	55.2	49.0
340.0	0.07	52.0	46.6
380.0	0.08	44.9	45.5
460.0	0.08	39.3	42.5
500.0	0.09	39.4	42.1
550.0	0.10	41.6	43.7
600.0	0.10	47.6	45.8
650.0	0.10	62.2	46.3
700.0	0.11	46.8	45.8
750.0	0.11	41.7	45.0
800.0	0.11	40.2	43.8
850.0	0.12	40.8	43.4
900.0	0.12	43.1	43.0
950.0	0.13	48.7	42.5
1000.0	0.13	55.0	42.6
1200.0	0.15	41.7	42.6
1400.0	0.16	45.3	42.9
1500.0	0.17	44.3	46.6
1800.0	0.18	40.5	42.2
1900.0	0.19	43.6	40.1
2000.0	0.19	40.2	37.3
2400.0	0.21	37.1	37.0
2600.0	0.22	44.8	39.8
2800.0	0.23	35.5	35.6
3000.0	0.24	44.4	39.6
3400.0	0.26	35.4	35.3
3600.0	0.27	37.7	36.3
4000.0	0.29	41.2	38.6
4400.0	0.31	38.8	39.5
4600.0	0.32	31.1	30.9
5000.0	0.33	35.2	35.2
5400.0	0.34	41.0	42.7
5600.0	0.35	31.8	32.2
6000.0	0.37	34.5	34.6
6400.0	0.38	42.3	44.8
6600.0	0.39	32.4	33.1
7000.0	0.41	32.4	32.0
7400.0	0.42	41.4	49.2
7600.0	0.42	34.0	31.8
8000.0	0.44	38.5	34.8
8400.0	0.45	45.5	41.3
8600.0	0.46	33.5	35.1
9000.0	0.47	35.0	40.7
9400.0	0.48	32.9	34.8
9600.0	0.49	29.8	32.4
10000.0	0.50	31.4	33.3
11200.0	0.54	40.8	41.5
11600.0	0.55	38.7	35.1
12000.0	0.57	44.0	37.3
12400.0	0.58	34.7	33.0
13600.0	0.61	35.9	41.6
14000.0	0.62	40.4	35.4
14400.0	0.64	41.8	38.0
15600.0	0.67	27.3	28.0
16000.0	0.67	27.3	28.1
16400.0	0.69	29.3	30.6
17600.0	0.74	27.8	30.4
18000.0	0.72	25.2	28.5