


WIRING INFORMATION

J1	Wire color	J2
2-e	Rose	2-e
1-e	Orange	1-e
2-d	Yellow	2-d
1-d	Rose	1-d
2-c	Rose	2-c
1-c	Brown	1-c
2-b	Black	2-b
1-b	Rose	1-b
2-a	Rose	2-a
1-a	Red	1-a
Shell	Braid	Shell



NOTES /

- 1.) CABLE ASSEMBLY IS MANUFACTURED PER RELEVANT JOB.
- 2.) MECHANICAL REQUIREMENTS
  - OPERATING TEMPERATURE = -20° TO +105°C
  - MATING CYCLES : 250, PERFORMANCE LEVEL 2 ( IEC 60512-5 )
- 3.) THE CONNECTOR COMPLIES REQUIREMENT : IEC 61076-4-107
- 4.) WHITE LABEL INFORMATION:

DATE CODE  
HARTING P/N

- 5.) CABLE MUST BE PERFORMED HI-POT TEST AND CONTINUITY TEST
- 6.) CABLE MUST BE PACKED INTO A PLASTIC BAG.

Rev.	Description	Appr.	Date
A	Prototype	Lucy Zheng	28/06/17

Part-No.	Scale	Free size tol.	Ref.	Sub.	Date	State
33 27 243 700 0019	/	/	/	/	2017-06-28	Final release
33 27 242 120 0055	/	/	/	/		
33 27 243 350 0029	/	/	/	/		
33 27 243 400 0028	/	/	/	/		
33 27 243 300 0027	/	/	/	/		
33 27 243 060 0026	/	/	/	/		
33 27 242 100 0021	/	/	/	/		
33 27 243 800 0020	/	/	/	/		
33 27 243 650 0019	/	/	/	/		
33 27 243 200 0003	/	/	/	/		
33 27 243 100 0002	/	/	/	/		
33 27 243 050 0001	/	/	/	/		

All Dimensions in mm		Scale	Free size tol.	Ref.	Sub.	Date	State
Original Size DIN A3		/	/	/	/	2017-06-28	Final release

All rights reserved		Created by	Inspected by	Standardisation	Date	State
HARTING		ZHENGL	LJK	LJK	2017-06-28	Final release

Department		Title		Type	Number	Rev.
HCS - CN		Har-link standard cable,male double ended cable assy, L*M		TB	33 27 0001	A

HARTING Customised Solutions		Doc-Key / EGM-Nr.		Page
D-32427 Minden		/		1/1