

# Product data sheet

## Miniature connectors




Product description	<b>M16 IP67 Male cable connector, Contacts: 8 (08-a), 4.0-6.0 mm, shieldable, solder, IP68, UL, AISG compliant</b>
Area	<b>M16 IP67 series 423</b>
Part no.	<b>99 5171 15 08</b>


### Illustration



### Scale drawing



### Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

## Technical data

### General features

Part no.	<b>99 5171 15 08</b>
Connector design	Male cable connector
Version	Connector pin straight
Connector locking system	screw
Termination	solder
Degree of protection	IP68 IP67
Cross-sectional area	max. 0.75 mm <sup>2</sup> / AWG 18
Cable outlet	4.0-6.0 mm
Temperature range from/to	-30 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	50.62
Customs tariff number	85369010

### Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Rated current (40 °C)	5.0 A
Insulation resistance	$\geq 10^{10} \Omega$
Pollution degree	1
Overvoltage category	I
Insulating material group	III
EMC compliance	shieldable
Shield connection	Shielding ring

# Product data sheet

## Miniature connectors



Product description	<b>M16 IP67 Male cable connector, Contacts: 8 (08-a), 4.0-6.0 mm, shieldable, solder, IP68, UL, AISG compliant</b>
Area	<b>M16 IP67 series 423</b>
Part no.	<b>99 5171 15 08</b>

### Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PBT (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Ag (silver)
REACH SVHC	CAS 96-45-7 (Imidazolidine-2-thione) CAS 7439-92-1 (Lead)
SCIP number	66f133e5-db93-45e7-87e1-6dcfd49c6bb5

### Authorization/approvals

Approvals	UL, AISG compliant
-----------	--------------------


### Classifications

eCl@ss 11.1	27-44-01-02
ETIM 7.0	EC002635

### Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)
-----------------------	--

### Assembly instructions



Product description	<b>M16 IP67 Male cable connector, Contacts: 8 (08-a), 4.0-6.0 mm, shieldable, solder, IP68, UL, AISG compliant</b>
Area	<b>M16 IP67 series 423</b>
Part no.	<b>99 5171 15 08</b>

### **General Disclaim Notice**

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).