



HARWIN

Component Specification

C02912

Archer
M50 and M52 Series Connectors
November 2022

SECTION	TITLE	PAGE
1	Description of Connector and Intended Application	2
2	Ratings	2

1. DESCRIPTION OF CONNECTOR AND INTENDED APPLICATION

A range of 1.27mm pitch connectors, jumper sockets and IDC cable connectors, comprising vertical surface mount, vertical and horizontal throughboard, plugs and sockets of varying heights. Board-to-board spacing and configuration is obtained by the selection of an appropriate height plug and socket.

- M50 connectors are spaced 1.27mm between rows and based on 0.40mm square/round pins.
- M52 connectors are spaced 2.54mm between rows and based on 0.46mm square pins.

2. RATINGS

Note:

- Individual components may exceed below ratings – check individual customer information sheets.
- For M50 Pin Header variants, use the relevant specifications for M50-350, 360 and 390. For M52 Pin Header variants, these are specified as "M52-PH".

2.1. Material & Finish

All materials are listed on individual drawings.

Housing Material:

PCB connectors	High Temperature Thermoplastic, UL94V-0, Black
IDC Cable connectors.....	30% Glass Filled PBT, UL94V-0 Black
Jumper Sockets	30% Glass Filled PBT, UL94V-0
Contact Material.....	Copper alloy

Contact Finish:

M50-380	Nickel all over, Gold Flash on contact area
Other connectors: 42 finish code.....	Nickel all over, Gold Flash on contact area, 100% Tin on tails
Other connectors: 45 finish code.....	Gold Flash over Nickel

2.2. Electrical Characteristics

Current Rating (per contact):

M50-355, M50-365	1.75A max
M50-380, M50-90X, M50-91X.....	0.5A max
Others.....	1A max

Contact Resistance..... 20mΩ max (initial),
30mΩ max (after conditioning)

Dielectric Withstanding Voltage (Voltage Proof):

M50-380	1,000V AC _{rms} for 1 minute
M50-310/312/430/470/480/490	300V AC, 500V DC for 1 minute
M50-311	1,000V AC for 1 minute (initial), 250V AC for 1 minute (final)
M50-303/313/314/315/330/350/353/355/363/365/390/393	500V AC for 1 minute (initial), 250V AC for 1 minute (final)
M50-19X/20X/320	800V AC _{rms} for 1 minute
M50-90X/91X	300V DC for 10 seconds
M52-500/510	500V AC, 1,000V DC for 1 minute
Others.....	1,000V AC _{rms} /DC for 1 minute

Insulation Resistance:

M50-355/365	5,000MΩ min
M50-310/312/430/470/480/490	500MΩ min
M50-90X/91X	5MΩ min
Others.....	1,000MΩ min

2.3. Environmental Characteristics

Operating Temperature Range:

M50-355/365	-55°C to +125°C
M50-90X/91X	-20°C to +105°C
Others.....	-40°C to +105°C

Vibration:

M50-19X/20X/300/320/350/360/380/390, All M52	50-2,000Hz, 3.13G _{rms} , duration 45 mins
M50-303/313/314/311/315	10-55Hz, 10G, duration 2hrs
Others.....	Not tested

Shock:

M50-19X/20X/300/320/350/360/380/390, All M52	30G for 11ms
M50-311/315.....	50G for 11ms
M50-310/312/430/470/480/490	Not tested

2.4. Mechanical Characteristics

Durability:

M50-310/312/330/380/430/470/480/490/90X/91X	100 operations
M50-311	600 operations
M50-315.....	25 operations
M50-353/363/393	500 operations
Others.....	300 operations

Insertion force (maximum):

M50-19X/20X	10N
M50-320/330/380/90X/91X, M52-500/510	1N per contact
M50-310/312/430	2N per contact
M50-311	0.8N per contact
M50-300/303/313/314/315, M52-501/505/511/515	1.5N per contact

Withdrawal force (minimum):

M50-19X/20X	1.3N
M50-310/312/315/330/380/430/90X/91X	0.15N per contact
M50-320, M52-500/510	0.12N per contact
M50-300, M52-501/505/511/515	0.1N per contact
M50-303/313/314.....	0.2N per contact

Contact Retention force (minimum):

M50-19X/20X	4N
M50-300/320/350/360/390, M52-PH/501/505/511/515	9.8N per contact
M50-310/312/430/470/480/490, M52-500/510	1.5N per contact
M50-303/311/313/314/315	3N per contact
M50-353/363/393	2N per contact

2.5. Soldering Data

Solderability (PCB connectors):

M50-311	230°C for 3 seconds
M50-315.....	260°C for 3 seconds
Others.....	245°C for 5 seconds

Soldering heat resistance (PCB connectors) 260°C for 10 seconds