



50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 18 GHz

TECHNICAL DATA SHEET

PE6074

50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 18 GHz	
Configuration	
RF Load Design	Precision
Connector	SMA Female
Connector Specification	MIL-STD-348
Heat Sink	Passivated Stainless Steel
Electrical Specifications	
Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Maximum VSWR	1.25:1
Maximum Input Power, Watts	1
Mechanical Specifications	
Size	
Length, in [mm]	0.6 [15.24]
Width/Dia., in [mm]	0.25 [6.35]
Connector	
Туре	SMA Female
Body Material and Plating	Passivated Stainless Steel
Compliance Certifications (visit www.Pasterna	ack.com for current document)
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
	Steel SMA Female RF Load With Chain Up To 18 GHz from Pasternack c and International orders. Our RF, microwave and fiber optic products adest selection in the industry.
	SEARCH" on website) to obtain additional part information including price, ision Passivated Stainless Steel SMA Female RF Load With Chain Up To

URL: http://www.pasternack.com/sma-female-precision-termination-pe6074-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com PE6074 CAD Drawing

50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 18 GHz

