

## Technical data sheet

### Connection unit

Part no.: 50031256

MA 2

#### Contents

- Technical data
- Electrical connection
- Operation and display
- Accessories



Figure can vary



# Technical data

## Basic data

Series	MA 2
Suitable for	BCL 2x series bar code readers LSIS 222 series stationary 2D-code readers

## Interface

Type	RS 232, RS 485
------	----------------

## Connection

Number of connections	3 Piece(s)
-----------------------	------------

### Connection 1

Function	Data interface PWR / SW IN / OUT
Type of connection	Terminal
No. of pins	24 -pin

### Connection 3

Function	Service interface
Type of connection	Sub-D

## Mechanical data

Dimension (W x H x L)	119 mm x 33 mm x 180 mm
Housing material	Metal
Net weight	575 g

## Environmental data

Ambient temperature, operation	-10 ... 50 °C
Ambient temperature, storage	-20 ... 60 °C
Relative humidity (non-condensing)	0 ... 90 %

## Certifications

Degree of protection	IP 54
----------------------	-------

## Classification

Customs tariff number	84733080
eCl@ss 5.1.4	27069190
eCl@ss 8.0	27069190
eCl@ss 9.0	27069190
eCl@ss 10.0	27069190
eCl@ss 11.0	27069090
ETIM 5.0	EC001855
ETIM 6.0	EC001855
ETIM 7.0	EC001855

# Electrical connection

## Connection 1

Function	Data interface PWR / SW IN / OUT
Type of connection	Terminal
Cable gland	PG11
No. of pins	24 -pin

## Pin Pin assignment

1	RS 485 A / RS232 CTS
2	RS 485 A / RS232 CTS
3	RS 485 B / RS232 RTS
4	RS 485 B / RS232 RTS
5	RS 485 GND / RS232 GND
6	RS 485 GND / RS232 GND
7	res. / SE2
8	n.c.
9	SE 1
10	n.c.
11	VDD_SE

## Electrical connection

Pin	Pin assignment
12	GND_SE
13	res. / SA2
14	SA1
15	n.c.
16	GND_SA
17	V_IN
18	V_IN
19	GND_IN
20	GND_IN
21	PE
22	PE
23	RxD
24	TXD

### Connection 3

Function	Service interface
Type of connection	Sub-D
No. of pins	9 -pin
Type	Male

Pin	Pin assignment
1	n.c.
2	RxD_Serv
3	TxD_Serv
4	n.c.
5	GNDIN
6	n.c.
7	RS 232 RTS
8	RS 232 CTS
9	n.c.

## Operation and display

LED	Display	Meaning
1	Green	Switching output/switching state

# Accessories

## Connection technology - Interconnection cables

	Part no.	Designation	Article	Description
	50035355	KB 031-3000	Interconnection cable	Suitable for interface: RS 232, RS 485 Connection 1: Sub-D, Axial, Female, 15 -pin Connection 2: JST ZHR Shielded: Yes Cable length: 3,000 mm

**Note**

A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.