



## **SUMMARY**

#### # Wires

Low voltage 4



Image is for illustrative purpose only

Series 00

**Termination type** Female solder

IP rating 50

AWG wire size 34.00 - 28.00

Cable Ø 0.00 - 0.00 mm

**Status** active

Matching parts FGG.00.304.CLAD35Z

### **Download**

Request a quote

Eplan Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

**Shell Style/Model** EG\*: Fixed receptacle, nut fixing

**Keying** 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material

Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290]

brass latch sleeve and mid pieces

Weight 2.63 g

#### **Performance**

Configuration 00.304 : 4 Low Voltage Insulator L: PEEK (UL 94 / V-0/1.5)

Rated Current 2 Amps

## **Specifications**

Contact Type: Solder

Contact Dia.: 0.5 mm (0.02in) Bucket Dia.: 0.4 mm (0.016in)

Max. Solid Conductor: 0.09 mm<sup>2</sup> (AWG 28) Max. Stranded Conductor: 0.05 mm<sup>2</sup> (AWG 30)

R (max): 8.7 mOhm


Vtest (contact-shell): 650 V (AC), 920 V (DC) Vtest (contact-contact): 800 V (AC), 1130 V (DC)


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### **Others**

Salt Spray Corrosion: >1000 hr

# **DRAWINGS**







#### **Dimensions**

	А	В	Е	L	М	N	S1	<b>S</b> 3	e
mm.	8	10.3	6	15.5	1	13.7	6.3	9	M7x0.5
in.	0,31	0,41	0,24	0,61	0,04	0,54	0,25	0,35	

# **RECOMMENDED BY LEMO**

## **Tools**

## **Cables**

CMN.04.T28.031PGCE	PVC	GREY	
CMN.04.T28.031PGZE		Grey	▶ €
CMN.04.T28.031PNCE	PVC	Black	
CMN.04.T28.031PNZE			▶——€

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CMN.04.T28.031QGC	TPR	Grey	
40080	PVC	Black	
40086	PVC	Blue	
4041	PVC	Grey	<b>∍</b>
4050	PVC	Black	
4080	PVC	Grey	
417920	PVC	Grey	
4280	PVC	Black	
80080	PVC	Grey	
80082	PVC	Red	
80084	PVC	Black	
CTR.75.030.121870G	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.