

FI-X30SSLA-HF

Product Details



Part Number	FI-X30SSLA-HF
Status	Active
Features	1.0mm pitch, for interface of LCD, Standard type (Board face mounting), 30 pos., Board side receptacle
Number of Positions	30 pos.
Contact Pitch (mm)	1.0 mm
Connector Type	Board side receptacle
Connector Style	Right angle
Wire Termination Style	-
PCB Mounting Method	Soldering (SMT)
Applicable Wire	-
Applicable Wire Size	-
Applicable Wire Insulation Diameter (mm)	-
Remarks on Applicable Wire	-
Material of Contact	Copper alloy

Finish of Contact in Connecting Area	Gold plating over Nickel
Finish of Contact in Terminal Area	-
Finish of Contact in PCB Mounting Area	Tin plating over Nickel
Shell, Material/ Finish	Stainless-steel/ Tin plating
Material of Housing	Heat resisting plastic (UL94V-0)
Locking Feature	Mechanical lock
PCB Mounted Height (mm)	2.3
Applicable Contacts	-
Applicable Product Part Numbers	
Packaging Type	
Quantity in The Standard Packaging (pieces)	
Documents	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> Drawings </div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> 3D Models </div> </div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center; margin-top: 5px;"> PDF Download </div>
Stock Search	<div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> Stock Search </div>
RoHS compliant	10 substances (2011/65/EU, (EU)2015/863)
REACH compliant	223 substances (17/01/2022)
Environment Information	<div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> RoHS/Reach Certificate </div>

Combination	FI-X30HL FI-X30M-NPB FI-X30HL-B FI-X30C-NPB FI-X30MR-NPB FI-X30MA1
Remarks	

Notice

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.

3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

- * Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

- * We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

*Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc