

Part Number: 39000038

Product Description: Mini-Fit Female Crimp Terminal, Tin (Sn) over Copper (Cu) Plated

Brass, 18-24, 22+22 AWG, Reel

Series Number: 5556

Status: Active

Product Category: Crimp Terminals

Engineering Number: 5556T

Packaging Alternative: 0039000039 (Bag)



Documents & Resources

Drawings

Drawing 039000038_sd.pdf

Packaging Design Drawing 55560001-PK-000.pdf Packaging Design Drawing SPK-5556-001-001.pdf Packaging Design Drawing SPK-5556-001-002.pdf Packaging Design Drawing SPK-5556-001-003.pdf

Specifications

Application Specification 55560001-AS-000.pdf
Product Specification 55560002-PS-CH-000.pdf
Product Specification 55560002-PS-ES-000.pdf
Product Specification 55560002-PS-SK-000.pdf
Product Specification 55560008-TS-000.pdf
Product Specification PS-5556-001-001.pdf
Product Specification PS-5556-002-001.pdf
Test Summary 55560000-TS-000.pdf
Test Summary 55560010-TS-000.pdf
Test Summary TS-5556-002-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44 |
|--------------------|--------------------------------|
| China RoHS | © |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |

| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
|------------|---|
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Crimp Terminals |
| Series | 5556 |
| Description | Mini-Fit Female Crimp Terminal, Tin (Sn) over Copper (Cu) Plated Brass, 18-24, 22+22 AWG, Reel |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Product Family | Mini-Fit Family Power Connectors |
| Product Name | Mini-Fit |
| UPC | 800753585010 |

Electrical

| Current - Maximum per Contact | 9.0A |
|-------------------------------|------|
| Voltage - Maximum | 600V |

Physical

| Durability (mating cycles max) | 30 |
|--------------------------------|--------|
| Gender | Female |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |

| Material - Plating Termination | Tin |
|--------------------------------|-----------------------|
| Net Weight | 0.182/g |
| Packaging Type | Reel |
| Plating min - Mating | 0.889µm |
| Plating min - Termination | 0.889µm |
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter | 1.30-3.10mm |
| Wire Size (AWG) | 18, 20, 22, 22+22, 24 |
| Wire Size mm ² | N/A |

Solder Process Data

| Lead-Free Process Capability | N/A |
|------------------------------|-----|
|------------------------------|-----|

Use with Part(s)

| Description | Part Number |
|--|--------------|
| Mini-Fit Jr. Receptacle Housings | <u>5557</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | <u>44516</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | <u>42474</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | <u>43760</u> |

Application Tooling

Global

| Description | Part Number |
|--|-------------------|
| Extraction Tool for Mini-Fit Jr. Terminals | <u>0011030044</u> |
| FineAdjust Applicator for Mini-Fit Double Crimp Applications Using Two 22 AWG Wires | <u>2037026300</u> |
| PremiumGrade Hand Crimp Tool for Mini-Fit Jr. Male and Female Terminals, 18-24 AWG | <u>0638190901</u> |
| FineAdjust Applicator for 18-20 AWG and 18-24 AWG Wires with Insulation Diameter 1.90-2.30mm | <u>0639015600</u> |

| FineAdjust Applicator for Insulation OD 1.40-1.70mm - 18-24 AWG | 0639023900 |
|---|-------------------|
| FineAdjust Applicator for Insulation OD 2.50-2.95mm Optimized for 18 AWG Only | 0639024800 |
| FineAdjust Applicator for Insulation OD 2.30-2.60mm - 18-24 AWG | 0639024900 |
| FineAdjust Applicator for Insulation OD 2.50-2.95mm, 18-24 AWG | 0639047800 |
| FineAdjust Applicator for Insulation OD 1.65-2.05mm, 18-24 AWG | 0639048000 |
| T2 Terminator for Insulation OD 1.90-2.30mm - 18-24 AWG | <u>0639115600</u> |
| T2 Terminator for insulation OD 1.40-1.70mm - 18-24 AWG | 0639123900 |
| T2 Terminator for insulation OD 2.50-2.95mm optimized for 18 AWG only | <u>0639124800</u> |
| T2 Terminator for insulation OD 2.30-2.60mm - 18-24 AWG | <u>0639124900</u> |
| T2 Terminator for Mini-Fit Crimp Terminals, 18-24 AWG with Large Insulation ODs | <u>0639147800</u> |
| T2 Terminator for Mini-Fit Crimp Terminals, 18-24 AWG with Smaller Insulation ODs | <u>0639148000</u> |

Application Tooling

Japan

| Description | Part Number |
|--|-------------|
| S-1 Applicator for Mini-Fit Plug and Receptacle Terminals, 18-24 AWG, UL1007 Wires | 0570223700 |
| S-1 Applicator for Mini-Fit Plug and Receptacle Terminals, 18-24 AWG, UL1015 Wires | 0570223710 |
| Hand Extraction Tool | 0570316000 |