FFA.00.250.CTAC29Z





Summary

Request a quote

Catalog		
Conv	1	
Coax	1	
Plug	Plug - Straight	
Locking system	Push-pull	
Jacket cable outside diameter [mm]	2.80 - 3.10 mm	
Matching parts	ERA.00.250.CTL	
Series	00 - NIM-CAMAC	

Technical details

Electrical Configuration


Coax	1
Contact Termination Coax	Solder
R (max)	6.1 mOhm
Insert configuration value	0.25 - 1 Coax (50 Ohm)
Insulator	T: PTFE
Rated current	4 Amps
Impedance	50 Ohm
VSWR	1.09 + 0.11 * f/GHz
Vtest	2100 V (AC), 3000 V (DC)
Contact Type	Coaxial 50 Ohm (Solder)
Test voltage	2.1 kV (rms)
Cable type	RG 316 /U
Bucket Dia.	0.6 mm (0.024in)
Contact Dia.	0.7 mm (0.028in)
Form & Material	
Shell style / Model id	FFA - Straight plug with cable collet and nut for fitting a bend relief
Plug	Straight
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	Circular, male
Variant	Nut for fitting a bend relief
Weight	3.73 g
Environment	
Environmental protection	IP50
F ret (min)	100 N
Salt Spray Corrosion	>1000 hr

Cable fixation

Cable termination protection	For cable bend relief	
Fixation type	Cable collet	
Jacket cable outside diameter [mm]	2.80 - 3.10 mm	

Drawings







Dimensions

	A	М	L
mm.	6.4	25.5	33.5
in.	0.25	1	1.32

Recommended By Lemo

Accessories

Tools	
Spanner wrench	DCD.00.ZZZ.PA060

Cables

Cable PartNumber	Material	Colour	Cable image	
17420	PVC	Black		_
31600	PTFE	Brown		
CCX.50.RG1.74AU28N	PVC	Black		
CCX.50.RG1.74AU28N	PVC	Black		_
CCX.50.RG3.16U28M	PTFE	Brown		