

**Mechanical characteristics**

interface dimensions acc. to panel piercing mating life

**Components**

centre contact  
serrated lock washer  
other metal parts  
insulator  
gasket

**Electrical characteristics**

impedance  
frequency  
voltage proof  
insulation resistance  
contact resistance  
centre contact  
outer contact

**Environmental**

operation temp.  
panel sealing (one-sided)  
RoHS compliant

**Mechanische Eigenschaften**

Steckgesicht nach Montagebohrung Steckzyklen

**Bauteile**

Innenkontakt  
Fächerscheibe  
sonstige Metallteile  
Isolierung  
Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**

Betriebstemperatur  
Einbaudichtigkeit (einseitig)  
RoHS konform

IEC 60169-17  
Z004  
>500

**Materials / Material**


CuNi1Pb1P (C97)  
CuSn6  
CuZn39Pb3  
PTFE  
NBR 70

**Finish / Oberfläche**

NiP Au  
Cu2Ni5  
Cu2Ni5

50 Ω  
0-4 GHz  
1,5 kV<sub>eff</sub> / 50 Hz  
≥ 5 MΩ  
≤ 20 mΩ  
≤ 5 mΩ

-40°C / +85°C  
IP67 (IEC 60259) (a)  
2011/65/EU



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					14.01.2019	BJ	
				gepr./ appr.	21.01.2019	JA	ca./approx. 21,8
				Maßstab/ scale	Benennung/ title		
				2:1 (1:1)	TNC Bulkhead Adaptor TNC-Verbindungsstück		
				Untert./ doc. type	Zeichnungsnr./ drawing no.		
				K	J01014B2233		
				Ersatz für/ replaces			
				Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1			
a	30341	07.03.2019	BJ				