

**Mechanical characteristics**  
cables

interface dimensions acc. to assembly code  
 centre conductor  
 outer conductor  
 panel piercing  
 mating life

**Components**

centre conductor  
 outer conductor  
 nut  
 serrated lock washer  
 crimp ferrule  
 insulator  
 gasket

**Electrical characteristics**

impedance  
 frequency  
 return loss  
 insertion loss  
 voltage proof  
 insulation resistance  
 contact resistance  
 centre contact  
 outer contact

**Environmental**

operating temp.  
 panel sealing  
 RoHS compliant

**Mechanische Eigenschaften**

Kabel

Steckgesicht nach Montageanleitung  
 Innenleiter  
 Außenleiter  
 Montagebohrung  
 Steckzyklen

**Bauteile**

Innenleiter  
 Außenleiter  
 Mutter  
 Fächerscheibe  
 Crimprohr  
 Isolierung  
 Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflussdämpfung  
 Einfügedämpfung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
 Innenkontakt  
 Außenkontakt

**Umgebung**

Betriebstemperatur  
 Einbaudichtigkeit  
 RoHS konform

ⓑ G 7: KX 22A, KX 3B, RG-174/U, RG-188A/U, RG-316/U, MRC 100 Flex (0.48L/1.5AF) Draka

IEC 61169-16  
 B3116  
 crimp  
 crimp  
 Z010  
 >500



**Materials / Material**

copper alloy / Kupferlegierung  
 brass / Messing  
 brass / Messing  
 copper alloy / Kupferlegierung  
 copper / Kupfer  
 PTFE  
 NBR

**Finish / Oberfläche**

Cu2Ag5, NiP-Au ⓑ  
 CuSnZn3  
 CuSnZn3  
 nickel-plated / vernickelt  
 CuSnZn3

ⓐ -30°C / +100°C  
 IP 67 (IEC 60529)  
 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	15.10.2010	BJ	
			gepr./ appr.	21.10.2010	MA	ca./approx. 39,38
			Maßstab/ scale	Benennung/ title		
			2:1	N Bulkhead Jack N-Kabeleinbaubuchse		
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	 Maße/ dimensions: mm
				K	J01021A0203	
b	28473	16.02.2017	MA			Original : DIN A4
a	23870	24.04.2012	MA	Ersatz für/ replaces EWA30096-00		Blatt/ sheet 1 von/ of 1