

SMA Male to TNC Male Adapter



PE943

### **RF Adapters Technical Data Sheet**

### Configuration

- SMA Male Connector 1
- TNC Male Connector 2

### Features

- Max VSWR of 1.25:1 up to 18 GHz
- SMA Interface compliant with MIL-C-39012

### **Applications**

Allows Connection Between Series
General Purpose Test

### Description

Pasternack's PE9439 SMA male to TNC male adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to TNC adapter has a male to male gender configuration built of durable stainless steel. PE9439 SMA male to TNC male adapter operates to 18 GHz. The Pasternack RF adapter provides excellent VSWR of 1.25:1 maximum.

• 50 Ohms

Straight Body Geometry

TNC Interface compliant with MIL-C-39012

Gold Plated Beryllium Copper Contact

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.25:1	

### **Mechanical Specifications**

Size
Length
Width
Weight

1.65 in [41.91 mm] 0.625 in [15.88 mm] 0.08 lbs [36.29 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to TNC Male Adapter PE9439

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





SMA Male to TNC Male Adapter

## **RF Adapters Technical Data Sheet**

### **PE9439**

Description	Connector 1	Connector 2	
Туре	SMA Male	TNC Male	
Polarity	Standard	Standard	
Interface Specification	MIL-C-39012	MIL-C-39012	
Hex Size	5/16 in.	7/16 in.	

### **Material Specifications**

	Connector 1		Connector 2		
Descriptio	n Material	Plating	Material	Plating	
Туре	SMA Male		TNC Male		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
Body	Passivated Stainless Steel	Passivated Stainless Steel			
Coupling Nut	Passivated Stainless Steel	Passivated Stainless Steel			

#### **Environmental Specifications**

Temperature

**Operating Range** 

-65 to +125 deg C

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to TNC Male Adapter PE9439

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com







PE9439

#### **Typical Performance Data** dB **Return Loss** 0 -10 -20 -30 -40 -50 -60 -70 -80 2 0 GHz 8 10 12 14 18 4 6 16

### **RF Adapters Technical Data Sheet**

SMA Male to TNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to TNC Male Adapter PE9439

URL: https://www.pasternack.com/sma-male-tnc-male-straight-adapter-pe9439-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE9439 CAD Drawing SMA Male to TNC Male Adapter

