

KF-ET-620

Art.-Nr. 50137382

Lichtleiter, tastend

KF-ET-620

Part No. 50137382

fiber, reflective

Technische Daten

Lichtleiter Typ	standard
Betriebstemperatur	-55°C ... +70°C
Min. Biegeradius	R25
Außendurchmesser Lichtleiter	2x Ø2,2mm
Aktiver Durchmesser Faser	2x Ø1,0mm
Kleinste erkennbares Teil	Ø0,2mm
Gesamtlänge	2021mm

Specifications

Fiber type	standard
Operating temperature	-55°C ... +70°C
Min. bending radius	R25
Fiber jacket diameter	2x Ø2.2mm
Active fiber diameter	2x Ø1,0mm
Smallest detectable object	Ø0.2mm
Total length	2021mm

Features



- 1) Einstellung am Lichtleiterverstärker: max. Ansprechzeit, max. Verstärkung, min. Schaltschwelle /
Adjustment on fiber optics amplifier: max. response time, max. gain, min. switching threshold

Typische Grenzreichweite für helle Objekte (weiß 90%) ¹⁾ Typ. scanning range limit for light objects (white 90%) ¹⁾

LV463LXR	1200mm
LV463.XR	600mm
LV463B, LV463.XV	410mm
LV463	240mm
LV462	140mm
LV461	80mm

Maßzeichnung/Dimensioned drawing

