



Directional 35 dB N Coupler From 1 GHz
to 11 GHz Rated to 600 Watts

Couplers Technical Data Sheet

PE2236-35

Mechanical Specifications

Size

Length	3.85 in [97.79 mm]
Width/Dia.	0.8 in [20.32 mm]
Height	1.58 in [40.13 mm]
Weight	0.495 lbs [224.53 g]

Configuration

Package Type	Connectorized
Input Connector	N Female
Output Connector	N Female
Coupled Connectors	SMA Female

Environmental Specifications

Temperature

Operating Range	-40 to +80 deg C
-----------------	------------------

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	
REACH Compliant	12/17/2015

Plotted and Other Data

Notes:

Directional 35 dB N Coupler From 1 GHz to 11 GHz Rated to 600 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 35 dB N Coupler From 1 GHz to 11 GHz Rated to 600 Watts PE2236-35](http://www.pasternack.com/directional-35-db-n-coupler-1-11-ghz-600-watts-pe2236-35-p.aspx)

URL: <http://www.pasternack.com/directional-35-db-n-coupler-1-11-ghz-600-watts-pe2236-35-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE2236-35 CAD Drawing

Directional 35 dB N Coupler From 1 GHz to 11 GHz Rated to 600 Watts



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.1
.XXX	±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE2236-35

PE PASTERNAK
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAD FILE	040116	SCALE	N/A	SIZE	A	3045
----------	--------	-------	-----	------	---	------

FSCM NO. 53919