



50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant

TECHNICAL DATA SHEET

PE7077

50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant

Configuration

Design Fixed Matching Pad
Body Style Straight
Connector 1 SMA Female
Impedance 1 50 Ohms

Connector Specification 1 MIL-STD-348
Connector 2 F Male
Impedance 2 75 Ohms

Electrical Specifications

Frequency Range, GHz

Maximum VSWR

1.25:1

Maximum Attenuation, dB

5.7

Attenuation Accuracy

± 0.5

Maximum Input Power, Watts

Peak Power, Watts

Peak Power Duty Cycle, µs

Directionality

DC to 3

1.25:1

5.7

4.10.5

5.7

4.10.5

5.7

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.5

6.10.

Mechanical Specifications

Size

Length, in [mm] 1.29 [32.77] Width/Dia., in [mm] 0.43 [10.92]

Body Material and Plating Passivated Stainless Steel

Connector 1

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Passivated Stainless Steel, Nickel

Connector 2

Type F Male
Inner Conductor Material and Plating Brass, Nickel
Coupling Nut Material and Plating Brass, Nickel
Hex Size, in. 7/16
Torque, in-lbs [Nm] 15 [1.7]
Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant PE7077

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant

TECHNICAL DATA SHEET

PE7077

Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant PE7077

URL: http://www.pasternack.com/50-ohm-sma-female-75-ohm-f-male-matching-pad-pe7077-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7077 CAD Drawing 50 Ohm SMA Female To 75 Ohm F Male Matching Pad Operating From DC to 3 GHz RoHS Compliant

