

# Coaxial Low Noise Amplifier

## ZX60-83LN-S+

50Ω 0.5 to 8 GHz

### The Big Deal

- Extremely wideband, 0.5 to 8 GHz
- Low Noise, 1.4 dB @ 2 GHz
- High IP3, +34 dBm
- Excellent gain flatness  $\pm 0.9$  dB over 0.5 to 7 GHz @6V



CASE STYLE: GC957

### Product Overview

Mini-Circuits' ZX60-83LN-S+ is a wideband low noise connectorized amplifier providing a unique combination of low noise figure, high IP3 and flat gain over a very wide frequency range, supporting a wide range of sensitive, high-dynamic range receiver applications and many systems where high performance over wideband is needed. This design operates on a single 5 or 6V supply and comes in a rugged, compact unibody case (0.74 x 0.75 x 0.46") with SMA connectors, making it an excellent candidate for tough operating conditions and crowded system layouts.

### Key Features

Feature	Advantages
Ultra-wideband with excellent gain flatness, $\pm 0.9$ dB	Enables a single amplifier to be used in a wide range of applications including WiFi, LTE, S-Band radar, C-band SATCOM, defense, instrumentation and more.
Low noise over the whole band	Enables lower system noise figure performance.
High gain, 21 dB typ.	Reduces the number of gain stages, lowering component count and overall system cost.
High IP3: <ul style="list-style-type: none"><li>• +35.2 dBm at 2 GHz</li><li>• +28.5 dBm at 8 GHz</li></ul>	The combination of low noise and high IP3 makes the ZX60-83LN-S+ ideal for use in low noise receiver front end (RFE) as it gives the user the advantages of sensitivity and two-tone IM performance at both ends of the dynamic range.
Low operating voltage, 5V/6V	The amplifier achieves high IP3 using low voltage.
Rugged, unibody construction	Mini-Circuits unibody construction integrates the RF connector into the case body, providing high reliability and excellent survivability in critical applications.

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# Coaxial Low Noise Amplifier

50Ω 0.5 to 8 GHz

## ZX60-83LN-S+

### Features

- Low Noise figure, 1.4 dB at 2 GHz
- High IP3, 35 dBm typ. at 2 GHz
- High Pout, P1dB 20.7 dBm typ. at 2 GHz and 6V
- Excellent Gain flatness, ±0.9 dB over 0.5 to 7 GHz and 6V

### Applications

- WiFi
- WLAN
- UMTS
- LTE
- WiMAX
- S-band Radar
- C-band Satcom



Generic photo used for illustration purposes only

CASE STYLE: GC957

Connectors	Model
SMA	ZX60-83LN-S+

**+RoHS Compliant**

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Electrical Specifications at 25°C unless noted

Parameter	Condition (GHz)	V <sub>DD</sub> =6.0			V <sub>DD</sub> =5.0	Units
		Min.	Typ.	Max.	Typ.	
Frequency Range		0.5		8.0	0.5-8.0	GHz
Noise Figure	0.5	—	1.6	—	1.6	dB
	2.0	—	1.4	1.7	1.4	
	4.0	—	1.5	—	1.5	
	8.0	—	2.2	—	2.2	
Gain	0.5	—	21.8	—	21.0	dB
	2.0	19.9	22.1	24.3	21.3	
	4.0	—	21.5	—	20.8	
	8.0	—	19.2	—	18.7	
Input Return Loss	0.5		14.2		13.1	dB
	2.0		15.0		15.0	
	4.0		12.0		11.0	
	8.0		6.1		6.1	
Output Return Loss	0.5		12.9		13.7	dB
	2.0		10.0		11.0	
	4.0		18.0		18.0	
	8.0		12.9		12.6	
Output Power at 1dB Compression <sup>(1)</sup>	0.5		18.6		16.3	dBm
	2.0		20.7		19.1	
	4.0		19.6		17.6	
	8.0		18.0		17.3	
Output IP3	0.5		34.2		29.7	dBm
	2.0		35.2		30.0	
	4.0		31.0		27.0	
	8.0		28.5		26.2	
Device Operating Voltage (V <sub>DD</sub> )			6.0	—	5.0	V
Device Operating Current (I <sub>DD</sub> )		—	77	94	60	mA
Device Current Variation vs. Temperature <sup>2</sup>		—	-152	—	-109	μA/°C
Device Current Variation vs. Voltage			0.016		0.016	mA/mV
Thermal Resistance, junction-to-ground lead			47		47	°C/W

1. Current increases at P1dB to 109 mA typ. at +6V V<sub>DD</sub> and 88mA typ. at +5V V<sub>DD</sub>

2. (Current at 85°C - Current at -45°C)/130

### Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



[www.minicircuits.com](http://www.minicircuits.com) P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com


REV. B  
ECO-000670  
ZX60-83LN-S+  
ED-15070802  
DJ/CP/AM  
191113  
Page 2 of 4

### Absolute Maximum Ratings<sup>4</sup>

Parameter	Ratings
Operating Temperature (ground lead)	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Total Power Dissipation	0.95 W
Input Power (CW), Vd=5.6V	+19 dBm (5 minutes max.) +16 dBm (continuous)
DC Voltage	7 V

4. Permanent damage may occur if any of these limits are exceeded.  
Electrical maximum ratings are not intended for continuous normal operation.

### Outline Drawing



**!** NOTE: When soldering the DC connections, caution must be used to avoid overheating the DC terminal. See Application Note. [AN-40-010](#).

### Outline Dimensions (inch/mm)







A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	wt
.74	.75	.46	1.18	.04	.17	.45	.59	.33	.21	.22	.14	1.00	.37	.18	.106	grams
18.80	19.1	11.68	30.0	1.02	4.32	11.4	14.99	8.38	5.33	5.59	3.56	25.40	9.40	4.57	2.69	23.0

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



FREQUENCY (MHz)	GAIN (dB)		DIRECTIVITY (dB)		VSWR (:1)				POWER OUT @1 dB COMPR. (dBm)		NF (dB)		IP3 (dBm)	
	5V	6V	5V	6V	5V		6V		5V	6V	5V	6V	5V	6V
					IN	OUT	IN	OUT						
500	21.30	22.16	5.52	5.42	1.54	1.45	1.53	1.60	16.84	19.32	1.60	1.57	31.05	34.61
750	21.77	22.58	4.43	4.41	1.11	1.10	1.46	1.58	18.50	20.70	1.36	1.34	31.75	36.32
1000	21.83	22.61	4.27	4.29	1.16	1.20	1.52	1.65	19.23	21.06	1.29	1.28	31.96	36.52
1500	21.75	22.52	4.44	4.47	1.28	1.31	1.51	1.64	20.08	21.68	1.32	1.31	36.35	38.37
2000	21.63	22.40	4.73	4.74	1.34	1.34	1.41	1.54	20.09	21.61	1.37	1.35	35.25	38.90
2500	21.45	22.22	5.17	5.15	1.39	1.36	1.32	1.43	19.79	21.14	1.52	1.50	33.23	38.19
3000	21.17	21.94	5.79	5.73	1.44	1.38	1.20	1.29	19.09	20.40	1.54	1.54	30.16	35.44
3500	21.16	21.91	5.96	5.88	1.55	1.47	1.10	1.17	18.00	19.67	1.59	1.55	29.93	35.24
4000	21.04	21.78	6.29	6.20	1.62	1.53	1.08	1.10	17.45	19.23	1.56	1.54	28.69	33.05
4500	20.89	21.60	6.59	6.52	1.67	1.58	1.13	1.08	18.21	19.70	1.56	1.55	29.82	35.40
5000	20.75	21.43	6.83	6.78	1.70	1.61	1.19	1.13	18.21	19.59	1.59	1.57	27.84	32.02
5500	20.72	21.37	6.96	6.95	1.75	1.66	1.25	1.18	18.88	19.98	1.57	1.57	29.37	33.90
6000	20.64	21.25	7.12	7.15	1.83	1.75	1.30	1.23	19.13	20.02	1.55	1.53	29.00	33.37
7000	20.02	20.58	8.53	8.58	2.26	2.18	1.42	1.36	18.89	19.61	1.90	1.87	29.40	33.74
8000	18.41	18.94	11.88	11.82	3.50	3.40	1.67	1.61	17.10	17.86	2.21	2.21	26.87	29.89



**Notes**

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

