

NEW!

Shielded Power Inductors—MSS1210H



- 12.3 × 12.3 mm footprint; 10 mm high shielded inductors
- 27 inductance values from 10 μH to 10 mH
- Low DCR and excellent current handling
- AEC-Q200 Grade 1 qualified (−40°C to +125°C ambient)
- **Designer's Kit C498** contains 3 of each part

Core material Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Environment RoHS compliant, halogen free

Terminations RoHS compliant matte tin over nickel over phos bronze. Other terminations available at additional cost.

Weight: 5.1– 6.2 g

Ambient temperature −40°C to +125°C with (40°C rise) Irms current.

Maximum part temperature +165°C (ambient + temp rise). [Derating](#).

Storage temperature Component: −55°C to +165°C.

Tape and reel packaging: −40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	Inductance ² (μH)	DCR (Ohms) ³		SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
		typ	max		10% drop	20% drop	30% drop	20°C rise	40°C rise
MSS1210H-103MED	10±20%	0.010	0.013	18.00	7.50	8.70	9.40	6.58	9.10
MSS1210H-153MED	15±20%	0.016	0.018	13.00	6.00	7.00	7.50	5.15	6.99
MSS1210H-223MED	22±20%	0.021	0.027	11.00	5.10	5.90	6.40	3.96	5.45
MSS1210H-333MED	33±20%	0.031	0.036	8.00	4.10	4.80	5.20	3.09	4.05
MSS1210H-473MED	47±20%	0.037	0.045	6.50	3.50	4.00	4.30	2.85	3.89
MSS1210H-683MED	68±20%	0.056	0.065	5.30	2.90	3.30	3.60	2.55	3.40
MSS1210H-104KED	100±10%	0.078	0.096	4.30	2.40	2.80	3.00	2.45	3.26
MSS1210H-124KED	120±10%	0.088	0.110	4.00	2.20	2.50	2.70	2.22	3.01
MSS1210H-154KED	150±10%	0.100	0.123	3.80	1.90	2.20	2.40	1.98	2.75
MSS1210H-184KED	180±10%	0.130	0.163	2.90	1.80	2.00	2.20	1.55	2.19
MSS1210H-224KED	220±10%	0.160	0.185	2.80	1.60	1.80	2.00	1.35	1.84
MSS1210H-334KED	330±10%	0.230	0.280	2.30	1.30	1.50	1.60	1.08	1.52
MSS1210H-474KED	470±10%	0.340	0.400	1.90	1.10	1.30	1.40	0.91	1.27
MSS1210H-684KED	680±10%	0.490	0.596	1.40	0.91	1.00	1.10	0.89	1.17
MSS1210H-105KED	1000±10%	0.630	0.768	1.30	0.75	0.87	0.94	0.68	1.07
MSS1210H-125KED	1200±10%	0.830	1.013	1.10	0.69	0.80	0.86	0.63	0.86
MSS1210H-155KED	1500±10%	0.970	1.178	1.00	0.61	0.71	0.77	0.58	0.82
MSS1210H-185KED	1800±10%	1.10	1.28	0.86	0.56	0.65	0.70	0.57	0.80
MSS1210H-225KED	2200±10%	1.50	1.75	0.82	0.51	0.59	0.63	0.46	0.63
MSS1210H-275KED	2700±10%	1.70	2.01	0.75	0.46	0.53	0.57	0.43	0.59
MSS1210H-335KED	3300±10%	2.20	2.70	0.63	0.41	0.48	0.52	0.38	0.53
MSS1210H-395KED	3900±10%	2.40	3.00	0.58	0.38	0.44	0.48	0.37	0.51
MSS1210H-475KED	4700±10%	2.70	3.35	0.53	0.35	0.40	0.43	0.35	0.48
MSS1210H-565KED	5600±10%	3.55	4.20	0.52	0.32	0.37	0.40	0.28	0.40
MSS1210H-685KED	6800±10%	4.00	4.82	0.50	0.29	0.33	0.36	0.27	0.39
MSS1210H-825KED	8200±10%	5.25	6.33	0.41	0.26	0.30	0.33	0.22	0.29
MSS1210H-106KED	10000±10%	5.95	7.10	0.38	0.24	0.27	0.30	0.22	0.30

1. Specify termination code:

MSS1210H-106KED

Termination: E = RoHS compliant matte tin over nickel over phos bronze.
Special order:
Q = RoHS tin-silver-copper (95.5/4/0.5) or
P = non-RoHS tin-lead (63/37).

Packaging: D = 13" machine-ready reel. EIA-481 embossed plastic tape (300 parts per full reel).


- Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc using an Agilent/HP 4263B LCR meter or equivalent.
- DCR measured on a micro-ohmmeter and a Coilcraft CCF858 test fixture.
- SRF measured using Agilent/HP 4191A or equivalent.
- DC current at 25°C that causes the specified inductance drop from its value without current.
[Click for temperature derating information.](#)
- Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
[Click for temperature derating information.](#)
- Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.





Shielded Power Inductors – MSS1210H

Typical L vs Current



Typical L vs Frequency



* For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.012 inch (0,3 mm).

Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Packaging 300/13" reel; Plastic tape: 24 mm wide, 0.5 mm thick, 20 mm pocket spacing, 10.3 mm pocket depth



US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1549-2 Revised 11/05/20

© Coilcraft Inc. 2020

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.